



999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake N3350/N4200 Processor
- 1 * SO-DIMM Dual CH DDR3L up to 8GB
- 2 * USB3.0, 6 * RJ45, 1 * RS232(RJ45 TYPE)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX POWER_200W

MB Model	– JNF692G6-335 / JNF692G6-420 (Mini-ITX) – JNF692G6-335B1 / JNF692G6-420B1 (Mini-ITX /1 pair support Bypass LAN)				
Part No	Standard	WIFI	Bypass LAN	Expansion 4 ports LAN PCI-E Card	Bypass LAN+ Expansion 4 ports LAN PCI-E Card
	– HBJC141F692-335B	– HBJC141F692W-335B	– HBJC141F692B-335B	– HBJC141F692-33G4	– HBJC141F692B-33G4
	– HBJC141F692-420B	– HBJC141F692W-420B	– HBJC141F692B-420B	– HBJC141F692-42G4	– HBJC141F692B-42G4
BIOS	– AMI 128MB SMT Flash ROM				
CPU/Chipset	– INTEL® Apollo Lake N3350/N4200 Processor				
Memory	– 1 * SO-DIMM slots DDR3L-1866MHz up to 8GB				
Storage	– 1 * 2.5" SATA3 6Gb/s internal drive bay – 1 * Full-size mSATA/mini-PCI Express shared slot				
Network	– 6 * Intel i211AT Gigabit LAN – 1 * Full-size mini-PCIe slot (802.11 b/g/n + BT 4.0 installed in WIFI model)				
Rear Panel I/O	– 1 * Power SWITCH – DC JACK				
Front Panel I/O	– 6 * RJ45 – 2 * USB3.0 – 1 * RS232 (RJ45 TYPE) – 1 * PW LED, 1 * Alarm LED – 1 * HDMI (Not assembled when shipped, wire placed in the parts box) – 1 * GPIO (Not assembled when shipped, wire placed in the parts box) – 2 * COM (optional)				
Power Source	– AC 90~240V input_DC12V-5A-60W out / FSP Adapter				
Compliance	– CE, FCC, RoHS				
Temperature	– Operating Temperature: 0 ~ 40° C – Storage Temperature: -10 ~ 70° C				
Dimensions	– 330 (W) x 192 (D) x 44 (H) mm				
Packing	– Net Weight: 1.6KG – Gross Weight: 2.6KG – Color Box dimension: 406 (W) * 148 (D) * 380 (H) mm				

OS Support	- Windows 10, Linux
Warranty	- 2 Year limited warranty