



879.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Celeron !
- Multi-Touch !
- 15" WXGA Panel Computer !

- 15" WXGA (1024 x 768) LED Display
- Projected Capacitive Multi Touch (P-CAP)
- Aluminum Front Bezel
- Fanless Intel® Celeron® Processor J6412
- Up to 32GB DDR4-3200, 2 x Intel 2.5GbE
- HDMI-out for 2nd Display
- VESA 100mm/Panel Mount Support
- Support TPM2.0 (option)
- DC-in 12V

## SYSTEM

|                |                                                                                                       |
|----------------|-------------------------------------------------------------------------------------------------------|
| PROCESSOR      | Intel® Celeron® Processor J6412 (formerly Elkhart Lake) , 2.0 GHz (Quad-Core), Burst frequency 2.6GHz |
| SYSTEM MEMORY  | 1 x DDR4 3200 Single Channel SODIMM, Non-ECC (Max.16GB, up to 3200MHz)                                |
| ETHERNET       | 2 x Intel® I225-V, 2.5GbE Base-TX                                                                     |
| STORAGE DEVICE | 1 x M.2 M-key 2242/2280 (SATA)<br>1 x 2.5" SATA-III Drive Bay                                         |

|                                        |                                                                                                                                                                                                                                                        |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| I/O                                    | 3 x DB9 Type COM port (2 x RS-232, 1 x RS-485)<br>4 x USB3.2 Gen 1<br>2 x USB2.0<br>1 x HDMI2.0b (Max. Resolution: 4096 x 2160@60Hz)<br>2 x RJ45 10/100/1000/2500 LAN<br>1 x DC-in 12V Jack (Lock type)<br>1 x Line-out<br>1 x MIC<br>1 x Power Button |
| EXPANSION                              | 1 x M.2 E-key 2230 (PCIe x1/USB2) (internal RP-SMA wires and Antenna pre-installed)                                                                                                                                                                    |
| CELLULAR (5G)                          | —                                                                                                                                                                                                                                                      |
| OS SUPPORT                             | Windows 10 (64bit), Windows 11 (enable PTT in BIOS)<br>Linux                                                                                                                                                                                           |
| <b>MECHANICAL</b>                      |                                                                                                                                                                                                                                                        |
| CONSTRUCTION                           | Aluminum Front Bezel + Metal Chassis                                                                                                                                                                                                                   |
| MOUNTING                               | VESA 100mm, Panel Mount                                                                                                                                                                                                                                |
| DIMENSIONS (W x H x D)                 | 367.4 x 291.4 x 72.5mm (14.46" x 11.47" x 2.85")                                                                                                                                                                                                       |
| CARTON DIMENSION                       | 597 x 357 x 483mm (23.50" x 14.06" x 19.02")                                                                                                                                                                                                           |
| GROSS WEIGHT                           | —                                                                                                                                                                                                                                                      |
| <b>ENVIRONMENT &amp; CERTIFICATION</b> |                                                                                                                                                                                                                                                        |
| OPERATING TEMPERATURE                  | -10°C ~ 60°C (14°F ~ 140°F) with 0.5 m/s airflow                                                                                                                                                                                                       |
| STORAGE TEMPERATURE                    | -20°C ~ 70°C (-4°F ~ 158°F)                                                                                                                                                                                                                            |
| STORAGE HUMIDITY                       | 90% @40°C (non-condensing)                                                                                                                                                                                                                             |
| VIBRATION                              | 1 Grms/ 5~ 500Hz/ operation                                                                                                                                                                                                                            |
| SHOCK                                  | —                                                                                                                                                                                                                                                      |
| CERTIFICATION                          | Meet CE/FCC Class A                                                                                                                                                                                                                                    |
| <b>POWER</b>                           |                                                                                                                                                                                                                                                        |
| INPUT                                  | DC-in 12V                                                                                                                                                                                                                                              |
| <b>LCD</b>                             |                                                                                                                                                                                                                                                        |
| DISPLAY TYPE                           | 15.0" TFT-LCD, LED                                                                                                                                                                                                                                     |
| MAX. RESOLUTION                        | 1024 x 768                                                                                                                                                                                                                                             |
| MAX. COLORS                            | 16.7M colors (8 bit for R,G,B)                                                                                                                                                                                                                         |
| LUMINANCE                              | 350 cd/m²                                                                                                                                                                                                                                              |
| VIEWING ANGLE                          | 178° (H), 178° (V)                                                                                                                                                                                                                                     |
| BACK LIGHT                             | LED                                                                                                                                                                                                                                                    |
| <b>TOUCH SCREEN</b>                    |                                                                                                                                                                                                                                                        |
| TYPE                                   | P-CAP Touchscreen                                                                                                                                                                                                                                      |
| LIGHT TRANSMISSION                     | 85%                                                                                                                                                                                                                                                    |